SUPER FRAME WORK

PROPERTIES

- Conforms to D3 according to DIN EN 204.
- Excellent bond strength on hard, and soft woods
- Water based
- Easy application

APPLICATIONS

- Suitable for gluing all types of wood, wooden materials and flat laminates,
- Wood to wood, soft- and hardboard, synthetic resin board and chipboard,
- Suitable for fixing paper, cardboard, paper or textile-backed PVC cloth to wood and board,
- May also be used to bond outdoor timber constructions such as window-frames and external doors,
- Particularly suitable for moisture-resistant bonds which have to fulfil high demands.

SUPER FRAME WORK

PROPERTIES

- High bond strength on numeroussubstrates
- Water based
- Easy application
- Dries transparent

APPLICATIONS

Suitable for bonding wood, decorative laminates, chipboard, blockboard etc. which have limited exposure to high humidity



SUPER FRAME WORK

Akfix D2 is a water based adhesive based on polyvinyl acetate homopolymer emulsion. It is specially formulated to conform to EN 204 (D2).



Akfix D3 is a ready to use water resistant wood adhesive based on polyvinyl acetate homopolymer emulsion. It is specially formulated to conform to EN 204 (D3).













info@akfix.com



CREATES PERMANENT SOLUTIONS



SUPER FRAME WORK

Akfix D2 is water based adhesive based on polyvinyl acetate homopolymer emulsion.

It is specially formulated to conform to EN 204 (D2).

RESISTANCE TO BACTERIOLOGICAL DEGRADATION

Strong Adhesion
HIGH WATER RESISTANCE







SUPER FRAME WORK

Akfix D3 is a ready to use water resistant wood adhesive based on polyvinyl acetate homopolymer emulsion. It is specially formulated to conform to EN 204 (D3).







High bond strength n numerous substrates

