ALL MATERIALS & ALL SURFACES





HIGH TACK

MULTI PURPOSE

MONTAGE ADHESIVE

High quality and professional adhesive with high adhesive strength and initial tack. It is suitable for bonding heavy building materials without the use of clamps and/or fixing tape.

350

SUPERIOR kg/10cm²


BONDING STRENGTH

5 SECONDS INITIAL TACK

FOR HEAVY

BUILDING MATERIALS

ALL MATERIALS & ALL SURFACES





HIGH TACK

MULTI PURPOSE MONTAGE ADHESIVE

FEATURES

- · High initial tack.
- Eco-friendly, free from isocyanate, solvent, acids and halogens.
- Excellent primerless adhesion to numerous porous and non-porous substrates.
- Excellent elasticity, no bubble formation, waterproof, no shrinkage, over-paintable.

APPLICATION AREAS

- It is specially developed as a universal adhesive for bonding various building materials.
- It is suitable for elastic bonding of panels, profiles and other pieces on the
 most common substrates such as: stone, concrete, mirrors, glass, plasterboard,
 PU, PVC, polyester, plastics, enamel, ceramic, copper, lead, zinc, aluminium,
 metals, R.V.S., wood, HPL and cement fibre panels etc. Common application
 areas are: Wall cladding elements and ceiling panels.
- Sound isolation panels (mineral wool, wood-wool cement & plastic foams).
- Thermal isolation panels (PUR, PIR, PS). Casings and frames in building construction.
- Wooden and plastic laths, ornaments and frames.
- Doorsteps, window sills, skirting boards and cover plates.
- Complete construction elements (such as roofing and facade elements) in frames.





